

VET KESÄTIISTAI 15 6 2021



Oil Pattern Distance Forward Oil Total Tank Configuration 39 10.44 mL N/A Reverse Brush Drop Reverse Oil Total Tank A Conditioner 36 8.24 mL TERRAIN Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 18.68 mL ICE

1 2L 4R 1 14 3 A 35 0.0 0.0 0.0 1400 2 4L 6R 1 14 3 A 29 1.9 1.9 1.9 1240 3 6L 6R 1 14 3 A 29 1.9 3.8 1.9 1160 4 8L 8R 3 14 3 A 75 3.8 9.7 5.9 3000 5 10L 10R 2 14 3 A 42 9.7 13.6 3.9 1680 6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0 9 2L 2R 0 26 3 A <	2 4L 6R 1 14 3 A 31 0.0 1.9 1.9 1240 3 6L 6R 1 14 3 A 29 1.9 3.8 1.9 1160 4 8L 8R 3 14 3 A 75 3.8 9.7 5.9 3000 5 10L 10R 2 14 3 A 42 9.7 13.6 3.9 1680 6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 6L 6R 1 14 3 A 29 1.9 3.8 1.9 1160 4 8L 8R 3 14 3 A 75 3.8 9.7 5.9 3000 5 10L 10R 2 14 3 A 42 9.7 13.6 3.9 1680 6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	3 6L 6R 1 14 3 A 29 1.9 3.8 1.9 1160 4 8L 8R 3 14 3 A 75 3.8 9.7 5.9 3000 5 10L 10R 2 14 3 A 42 9.7 13.6 3.9 1680 6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	1	2L	4R	1	14	3	Α	35	0.0	0.0	0.0	1400
4 8L 8R 3 14 3 A 75 3.8 9.7 5.9 3000 5 10L 10R 2 14 3 A 42 9.7 13.6 3.9 1680 6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	4 8L 8R 3 14 3 A 75 3.8 9.7 5.9 3000 5 10L 10R 2 14 3 A 42 9.7 13.6 3.9 1680 6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	2	4L	6R	1	14	3	Α	31	0.0	1.9	1.9	1240
5 10L 10R 2 14 3 A 42 9.7 13.6 3.9 1680 6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	5 10L 10R 2 14 3 A 42 9.7 13.6 3.9 1680 6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	3	6L	6R	1	14	3	Α	29	1.9	3.8	1.9	1160
6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	6 12L 12R 2 14 3 A 34 13.6 17.5 3.9 1360 7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	4	8L	8R	3	14	3	Α	75	3.8	9.7	5.9	3000
7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	7 13L 13R 1 14 3 A 15 17.5 19.4 1.9 600 8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	5	10L	10R	2	14	3	Α	42	9.7	13.6	3.9	1680
8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	8 2L 2R 0 22 3 A 0 19.4 29.0 9.6 0	6	12L	12R	2	14	3	Α	34	13.6	17.5	3.9	1360
		7	13L	13R	1	14	3	Α	15	17.5	19.4	1.9	600
9 2L 2R 0 26 3 A 0 29.0 39.0 10.0 0	9 2L 2R 0 26 3 A 0 29.0 39.0 10.0 0	8	2L	2R	0	22	3	Α	0	19.4	29.0	9.6	0
		9	2L	2R	0	26	3	Α	0	29.0	39.0	10.0	0

1 2	2L	STOP 2R		SPEED	BUFFER	TANK	CROSSED				
2 1		2R						START	END	FEET	T.OIL
	121		0	30	3	В	0	39.0	32.0	-7.0	0
		12R	1	22	3	В	17	32.0	28.9	-3.1	680
3 1	10L	10R	2	22	3	В	42	28.9	22.7	-6.2	1680
4 8	8L	8R	2	18	3	В	50	22.7	17.6	-5.1	2000
5 6	6L	6R	1	18	3	В	29	17.6	15.1	-2.5	1160
6 5	5L	5R	1	14	3	В	31	15.1	13.2	-1.9	1240
7 2	2L	2R	1	18	3	В	37	13.2	10.7	-2.5	1480
8 2	2L	2R	0	14	3	В	0	10.7	0.0	-10.7	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 59 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200





