

10 5 VET KESÄTIISTAI



Oil Pattern Distance Forward Oil Total Tank Configuration 42 11.64 mL N/A Reverse Brush Drop Reverse Oil Total Tank A Conditioner

7.44 mL TERRAIN

30

Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 19.08 mL ICE

25

22

45

8

35

25

2

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	18	3	Α	74	0.0	2.5	2.5	2960
2	4L	4R	2	18	3	Α	66	2.5	7.6	5.1	2640
3	6L	6R	2	22	3	Α	58	7.6	13.8	6.2	2320
4	8L	8R	1	22	3	Α	25	13.8	16.9	3.1	1000
5	10L	10R	1	22	3	Α	21	16.9	20.0	3.1	840
6	12L	12R	2	26	3	Α	34	20.0	27.3	7.3	1360
7	14L	14R	1	26	3	Α	13	27.3	30.9	3.6	520
8	2L	2R	0	30	3	Α	0	30.9	42.0	11.1	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	42.0	20.0	-22.0	0
2	5L	5R	2	18	3	В	62	20.0	14.9	-5.1	2480
3	5L	5R	2	18	3	В	62	14.9	9.8	-5.1	2480
4	5L	5R	2	18	3	В	62	9.8	4.7	-5.1	2480
5	2L	2R	0	14	3	В	0	4.7	0.0	-4.7	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 50 Combined
Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.13	1.21	1.01	1.01	1.21	2.13

