

21 6 VET KESÄTIISTAI



Oil Pattern Distance 35 **Reverse Brush Drop** 30 Oil Per Board 40 ul **Forward Oil Total** 10.56 mL **Reverse Oil Total** 11.2 mL **Volume Oil Total** 21.76 mL **Tank Configuration Tank A Conditioner TERRAIN Tank B Conditioner** N/A **ICE**

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	18	3	Α	74	0.0	2.5	2.5	2960
2	4L	4R	3	18	3	Α	99	2.5	10.1	7.6	3960
3	5L	5R	2	18	3	Α	62	10.1	15.2	5.1	2480
4	6L	6R	1	18	3	Α	29	15.2	17.7	2.5	1160
5	2L	2R	0	22	3	Α	0	17.7	35.0	17.3	0

1 2 2 8 3 7	BL	2R 8R 7R	0 1	30 22	3	В	0	25.0			
3 7			1	22			•	35.0	29.0	-6.0	0
	7L	7D			3	В	25	29.0	25.9	-3.1	1000
		/ K	1	22	3	В	27	25.9	22.8	-3.1	1080
4 6	6L	6R	1	22	3	В	29	22.8	19.7	-3.1	1160
5 5	5L	5R	2	18	4	В	62	19.7	14.6	-5.1	2480
6 4	4L	4R	2	14	4	В	66	14.6	10.7	-3.9	2640
7 3	3L	3R	1	14	4	В	35	10.7	8.8	-1.9	1400
8 2	2L	3R	1	14	4	В	36	8.8	6.9	-1.9	1440
9 2	2L	2R	0	14	4	В	0	6.9	0.0	-6.9	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 59 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
1.49	1	1	1	1	1.49
	Outside:Middle	Outside:Middle Middle:Middle	Outside:Middle Middle:Middle Inside:Middle	Outside:Middle Middle:Middle Inside:Middle MIddle: Inside	Outside:Middle Middle:Middle Inside:Middle MIddle:Inside Middle:Middle



