

76 VET KESÄTIISTAI



Oil Pattern Distance 40 **Reverse Brush Drop** 34 Oil Per Board 40 ul **Forward Oil Total** 13.72 mL **Reverse Oil Total** 6.12 mL **Volume Oil Total** 19.84 mL **Tank Configuration Tank A Conditioner TERRAIN Tank B Conditioner** N/A **ICE**

1 2L 2R 3 18 3 A 111 0.0 5.1 5.1 444 2 4L 4R 1 18 3 A 33 5.1 7.6 2.5 132 3 5L 5R 2 18 3 A 62 7.6 12.7 5.1 248 4 6L 6R 2 18 3 A 58 12.7 17.8 5.1 232 5 7L 7R 2 18 3 A 54 17.8 22.9 5.1 216 6 8L 8R 1 18 3 A 25 22.9 25.4 2.5 100
3 5L 5R 2 18 3 A 62 7.6 12.7 5.1 2480 4 6L 6R 2 18 3 A 58 12.7 17.8 5.1 2320 5 7L 7R 2 18 3 A 54 17.8 22.9 5.1 2160
4 6L 6R 2 18 3 A 58 12.7 17.8 5.1 2320 5 7L 7R 2 18 3 A 54 17.8 22.9 5.1 2160
5 7L 7R 2 18 3 A 54 17.8 22.9 5.1 216
6 8L 8R 1 18 3 A 25 22.9 25.4 2.5 100
7 2L 2R 0 26 3 A 0 25.4 40.0 14.6

3 11L 11R 2 18 3 A 38 11.8 6.7 -5.1 1 4 8L 8R 1 14 3 A 25 6.7 4.8 -1.9 1 5 7L 7R 1 14 3 A 27 4.8 2.9 -1.9 1	12L 12R 2 22 3 A 34 18.0 11.8 -6.2 1360 11L 11R 2 18 3 A 38 11.8 6.7 -5.1 1520 8L 8R 1 14 3 A 25 6.7 4.8 -1.9 1000 7L 7R 1 14 3 A 27 4.8 2.9 -1.9 1080 6L 6R 1 14 3 A 29 2.9 1.0 -1.9 1160	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 11L 11R 2 18 3 A 38 11.8 6.7 -5.1 1 4 8L 8R 1 14 3 A 25 6.7 4.8 -1.9 1 5 7L 7R 1 14 3 A 27 4.8 2.9 -1.9 1	11L 11R 2 18 3 A 38 11.8 6.7 -5.1 1520 8L 8R 1 14 3 A 25 6.7 4.8 -1.9 1000 7L 7R 1 14 3 A 27 4.8 2.9 -1.9 1080 6L 6R 1 14 3 A 29 2.9 1.0 -1.9 1160	2L	2R	0	30	3	Α	0	40.0	18.0	-22.0	0
4 8L 8R 1 14 3 A 25 6.7 4.8 -1.9 1 5 7L 7R 1 14 3 A 27 4.8 2.9 -1.9 1	8L 8R 1 14 3 A 25 6.7 4.8 -1.9 1000 7L 7R 1 14 3 A 27 4.8 2.9 -1.9 1080 6L 6R 1 14 3 A 29 2.9 1.0 -1.9 1160	12L	12R	2	22	3	Α	34	18.0	11.8	-6.2	1360
5 7L 7R 1 14 3 A 27 4.8 2.9 -1.9 1	7L 7R 1 14 3 A 27 4.8 2.9 -1.9 1080 6L 6R 1 14 3 A 29 2.9 1.0 -1.9 1160	11L	11R	2	18	3	Α	38	11.8	6.7	-5.1	1520
	6L 6R 1 14 3 A 29 2.9 1.0 -1.9 1160	8L	8R	1	14	3	Α	25	6.7	4.8	-1.9	1000
6 6L 6R 1 14 3 A 29 2.9 1.0 -1.9 1		7L	7R	1	14	3	Α	27	4.8	2.9	-1.9	1080
	2L 2R 0 14 3 A 0 1.0 0.0 -1.0 0	6L	6R	1	14	3	Α	29	2.9	1.0	-1.9	1160
7 2L 2R 0 14 3 A 0 1.0 0.0 -1.0		2L	2R	0	14	3	Α	0	1.0	0.0	-1.0	0
7			2L 12L 11L 8L 7L 6L	2L 2R 12L 12R 11L 11R 8L 8R 7L 7R 6L 6R	2L 2R 0 12L 12R 2 11L 11R 2 8L 8R 1 7L 7R 1 6L 6R 1	2L 2R 0 30 12L 12R 2 22 11L 11R 2 18 8L 8R 1 14 7L 7R 1 14 6L 6R 1 14	2L 2R 0 30 3 12L 12R 2 22 3 11L 11R 2 18 3 8L 8R 1 14 3 7L 7R 1 14 3 6L 6R 1 14 3	12L 12R 2 22 3 A 11L 11R 2 18 3 A 8L 8R 1 14 3 A 7L 7R 1 14 3 A 6L 6R 1 14 3 A	2L 2R 0 30 3 A 0 12L 12R 2 22 3 A 34 11L 11R 2 18 3 A 38 8L 8R 1 14 3 A 25 7L 7R 1 14 3 A 27 6L 6R 1 14 3 A 29	2L 2R 0 30 3 A 0 40.0 12L 12R 2 22 3 A 34 18.0 11L 11R 2 18 3 A 38 11.8 8L 8R 1 14 3 A 25 6.7 7L 7R 1 14 3 A 27 4.8 6L 6R 1 14 3 A 29 2.9	2L 2R 0 30 3 A 0 40.0 18.0 12L 12R 2 22 3 A 34 18.0 11.8 11L 11R 2 18 3 A 38 11.8 6.7 8L 8R 1 14 3 A 25 6.7 4.8 7L 7R 1 14 3 A 27 4.8 2.9 6L 6R 1 14 3 A 29 2.9 1.0	2L 2R 0 30 3 A 0 40.0 18.0 -22.0 12L 12R 2 22 3 A 34 18.0 11.8 -6.2 11L 11R 2 18 3 A 38 11.8 6.7 -5.1 8L 8R 1 14 3 A 25 6.7 4.8 -1.9 7L 7R 1 14 3 A 27 4.8 2.9 -1.9 6L 6R 1 14 3 A 29 2.9 1.0 -1.9

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 59 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Itom	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
ltem Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.65	1.18	1	1	1.18	2.65



