

VET KESÄTIISTAI 16 8 2022



Oil Pattern Distance Forward Oil Total Tank Configuration 43 9.76 mL Multi Tank Reverse Brush Drop Reverse Oil Total Tank A Conditioner

9.2 mL TERRAIN

30

Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 18.96 mL ICE

	CTART	CTOR	LOADS	CDCCD	BUFFER	TANK	CROCCER	CTART	ENID		T.OIL	
							CROSSED		END	FEET		
1	5L	5R	2	18	3	Α	62	0.0	2.5	2.5	2480	
2	8L	8R	2	18	3	Α	50	2.5	7.6	5.1	2000	
3	10L	10R	3	22	3	Α	63	7.6	16.9	9.3	2520	
4	12L	12R	2	22	3	Α	34	16.9	23.1	6.2	1360	
5	14L	14R	2	22	3	Α	26	23.1	29.3	6.2	1040	
6	16L	16R	1	26	3	Α	9	29.3	32.9	3.6	360	
7	2L	2R	0	26	3	Α	0	32.9	43.0	10.1	0	

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL	
1	2L	2R	0	30	3	В	0	43.0	28.0	-15.0	0	
2	12L	12R	2	22	3	В	34	28.0	21.8	-6.2	1360	
3	10L	10R	2	18	3	В	42	21.8	16.7	-5.1	1680	
4	9L	9R	2	18	3	В	46	16.7	11.6	-5.1	1840	
5	8L	8R	2	18	3	В	50	11.6	6.5	-5.1	2000	
6	6L	6R	2	14	3	В	58	6.5	2.6	-3.9	2320	
7	2L	2R	0	14	3	В	0	2.6	0.0	-2.6	0	

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 30 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
escription	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
rack Zone Ratio	11	1.64	1.05	1.05	1.64	11



