



Oil Pattern Distance	43	Reverse Brush Drop	33	Oil Per Board	45 ul
Forward Oil Total	13.365 mL	Reverse Oil Total	10.485 mL	Volume Oil Total	23.85 mL
Tank Configuration	Multi Tank	Tank A Conditioner	TERRAIN	Tank B Conditioner	ICE

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	1	14	3	A	37	0.0	0.0	0.0	1665
2	4L	5R	3	18	3	A	96	0.0	7.6	7.6	4320
3	6L	7R	3	18	3	A	84	7.6	15.2	7.6	3780
4	9L	9R	2	18	3	A	46	15.2	20.3	5.1	2070
5	12L	12R	2	22	3	A	34	20.3	26.5	6.2	1530
6	2L	2R	0	30	3	A	0	26.5	43.0	16.5	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	B	0	43.0	32.0	-11.0	0
2	12L	12R	2	22	3	B	34	32.0	25.8	-6.2	1530
3	9L	9R	2	22	3	B	46	25.8	19.6	-6.2	2070
4	7L	7R	3	22	3	B	81	19.6	10.3	-9.3	3645
5	3L	3R	1	18	3	B	35	10.3	7.8	-2.5	1575
6	2L	2R	1	18	3	B	37	7.8	5.3	-2.5	1665
7	2L	2R	0	14	3	B	0	5.3	0.0	-5.3	0



Cleaner Ratio Main Mix 24:1 Forward
 Cleaner Ratio Back End Mix 33:1 Reverse
 Cleaner Ratio Back End Distance 59 Combined
 Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.78	1.25	1	1	1.25	3.33

