

1. JAKSO BAY SYYSRYSÄYS



Oil Pattern Distance Forward Oil Total Tank Configuration

12.285 mL Multi Tank

40

Reverse Brush Drop Reverse Oil Total

Tank A Conditioner

11.475 mL TERRAIN

31

Oil Per Board Volume Oil Total Tank B Conditioner 45 ul 23.76 mL ICE

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	3R	3	18	3	Α	108	0.0	5.1	5.1	4860
2	4L	7R	2	18	3	Α	60	5.1	10.2	5.1	2700
3	8L	8R	2	18	3	Α	50	10.2	15.3	5.1	2250
4	11L	11R	2	18	3	Α	38	15.3	20.4	5.1	1710
5	12L	12R	1	22	3	Α	17	20.4	23.5	3.1	765
6	2L	2R	0	30	3	Α	0	23.5	40.0	16.5	0

2 10L 10R 1 26 3 B 21 30.0 26.4 -3.6 945 3 9L 9R 1 22 3 B 23 26.4 23.3 -3.1 1035 4 8L 8R 2 22 3 B 50 23.3 17.1 -6.2 2250 5 6L 6R 3 18 3 B 87 17.1 9.5 -7.6 3915 6 2L 2R 2 14 3 B 74 9.5 5.6 -3.9 3330		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 9L 9R 1 22 3 B 23 26.4 23.3 -3.1 1035 4 8L 8R 2 22 3 B 50 23.3 17.1 -6.2 2250 5 6L 6R 3 18 3 B 87 17.1 9.5 -7.6 3915 6 2L 2R 2 14 3 B 74 9.5 5.6 -3.9 3330	1	2L	2R	0	30	3	В	0	40.0	30.0	-10.0	0
4 8L 8R 2 22 3 B 50 23.3 17.1 -6.2 2250 5 6L 6R 3 18 3 B 87 17.1 9.5 -7.6 3915 6 2L 2R 2 14 3 B 74 9.5 5.6 -3.9 3330	2	10L	10R	1	26	3	В	21	30.0	26.4	-3.6	945
5 6L 6R 3 18 3 B 87 17.1 9.5 -7.6 3915 6 2L 2R 2 14 3 B 74 9.5 5.6 -3.9 3330	3	9L	9R	1	22	3	В	23	26.4	23.3	-3.1	1035
6 2L 2R 2 14 3 B 74 9.5 5.6 -3.9 3330	4	8L	8R	2	22	3	В	50	23.3	17.1	-6.2	2250
	5	6L	6R	3	18	3	В	87	17.1	9.5	-7.6	3915
7 2L 2R 0 14 3 B 0 5.6 0.0 -5.6 0	6	2L	2R	2	14	3	В	74	9.5	5.6	-3.9	3330
	7	2L	2R	0	14	3	В	0	5.6	0.0	-5.6	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 59 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Dunci Ki Wi	1 + - 000 0) = 300 Z =	- 300 1 - 20				
Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R	
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside	
Track Zone Ratio	2.44	1.16	1	1	1.16	2.88	
							_
1350							_



