

RKM UMACON 2023



Oil Pattern Distance **Forward Oil Total Tank Configuration**

11.84 mL Multi Tank

43

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

33 9.84 mL **TERRAIN** Oil Per Board **Volume Oil Total Tank B Conditioner**

40 ul 21.68 mL **ICE**

25

22

45

8

35

8

25

2

9

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	18		A	74		2.5		2960
	5L	5R	2				62		7.6		2480
	8L	8R	2	18			50		12.7	5.1	
	10L	10R	2	22	3		42		18.9		1680
	10L	10R	2	22		Α	42		25.1		1680
6	13L	13R	1	22	3	Α	15	25.1	28.2	3.1	600
7	15L	15R	1	22	3	Α	11	28.2	31.3	3.1	440
8	2L	2R	0	30	3	Α	0	31.3	43.0	11.7	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	43.0	28.0	-15.0	0
2	15L	15R	1	22	3	В	11	28.0	24.9	-3.1	440
3	13L	13R	1	22	3	В	15	24.9	21.8	-3.1	600
4	10L	10R	2	18	3	В	42	21.8	16.7	-5.1	1680
5	9L	9R	2	18	3	В	46	16.7	11.6	-5.1	1840
6	5L	5R	2	14	3	В	62	11.6	7.7	-3.9	2480
7	3L	3R	2	14	3	В	70	7.7	3.8	-3.9	2800
8	2L	2R	0	14	3	В	0	3.8	0.0	-3.8	0

Cleaner Ratio Main Mix 24:1 Forw Cleaner Ratio Back End Mix 33:1 Reve Cleaner Ratio Back End Distance 50 Com

8L-12L:18L-18R

1.45

13L-17L:18L-18R

1.04

Inside:Middle

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Outside:Middle Middle:Middle

3L-7L:18L-18R

3,44

Item

Track Zone Ratio

Description

3.0 4.9 1.8 5.7 1.6 7.7 3.8	24.9 21.8 16.7 11.6 7.7 3.8 0.0	-3.1 -3.1 -5.1 -5.1 -3.9 -3.9	600 1680 1840 2480 2800						
0_	Re	rwai vers mbii	e						
18L-18R:17R-13R			18L-18R:1	12R-8R	18L-18	ı			
Mlddle: Inside			Middle:Mi	ddle	Middle:				
1.04			1.45	5	3	.44			
									 -

