

6 6 VET KESÄTIISTAI



Oil Pattern Distance 43 **Reverse Brush Drop** 34 Oil Per Board 40 ul **Forward Oil Total** 9.92 mL **Reverse Oil Total** 9.2 mL **Volume Oil Total** 19.12 mL **Tank Configuration Tank A Conditioner Tank B Conditioner** Multi Tank **TERRAIN ICE**

1 4L 4R 2 18 3 A 66 0.0 2.5 2.5 26 2 8L 8R 2 18 3 A 50 2.5 7.6 5.1 20 3 10L 10R 3 22 3 A 63 7.6 16.9 9.3 25 4 12L 12R 2 22 3 A 34 16.9 23.1 6.2 10 5 14L 14R 2 22 3 A 26 23.1 29.3 6.2 10
3 10L 10R 3 22 3 A 63 7.6 16.9 9.3 25 4 12L 12R 2 22 3 A 34 16.9 23.1 6.2 13
4 12L 12R 2 22 3 A 34 16.9 23.1 6.2 13
5 14I 14R 2 22 3 A 26 23.1 29.3 6.2 10
3 112 1111 2 22 3 11 20 2311 2313 012 11
6 16L 16R 1 26 3 A 9 29.3 32.9 3.6 3
7 2L 2R 0 26 3 A 0 32.9 43.0 10.1

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	43.0	28.0	-15.0	0
2	12L	12R	2	22	3	В	34	28.0	21.8	-6.2	1360
3	10L	10R	2	18	3	В	42	21.8	16.7	-5.1	1680
4	9L	9R	2	18	3	В	46	16.7	11.6	-5.1	1840
5	8L	8R	2	18	3	В	50	11.6	6.5	-5.1	2000
6	6L	6R	2	14	3	В	58	6.5	2.6	-3.9	2320
7	2L	2R	0	14	3	В	0	2.6	0.0	-2.6	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 50 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	9.17	1.64	1.05	1.05	1.64	9.17



