

## **27 6 VET KESÄTIISTAI**



Oil Pattern Distance 42 **Reverse Brush Drop** 26 Oil Per Board 40 ul **Forward Oil Total** 11.36 mL **Reverse Oil Total** 8.64 mL **Volume Oil Total** 20 mL **Tank Configuration Tank A Conditioner TERRAIN Tank B Conditioner** Multi Tank **ICE** 

1     2L     2R     2     18     4     A     74     0.0     2.5     2.5     2960       2     6L     6R     2     22     4     A     58     2.5     8.7     6.2     2320       3     8L     8R     2     22     4     A     50     8.7     14.9     6.2     2000       4     10L     10R     2     22     4     A     42     14.9     21.1     6.2     1680       5     12L     12R     2     22     4     A     34     21.1     27.3     6.2     1360       6     14L     14R     2     22     4     A     26     27.3     33.5     6.2     1040		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3     8L     8R     2     22     4     A     50     8.7     14.9     6.2     2000       4     10L     10R     2     22     4     A     42     14.9     21.1     6.2     1680       5     12L     12R     2     22     4     A     34     21.1     27.3     6.2     1360       6     14L     14R     2     22     4     A     26     27.3     33.5     6.2     1040	1	2L	2R	2	18	4	Α	74	0.0	2.5	2.5	2960
4 10L 10R 2 22 4 A 42 14.9 21.1 6.2 1680 5 12L 12R 2 22 4 A 34 21.1 27.3 6.2 1360 6 14L 14R 2 22 4 A 26 27.3 33.5 6.2 1040	2	6L	6R	2	22	4	Α	58	2.5	8.7	6.2	2320
5 12L 12R 2 22 4 A 34 21.1 27.3 6.2 1360 6 14L 14R 2 22 4 A 26 27.3 33.5 6.2 1040	3	8L	8R	2	22	4	Α	50	8.7	14.9	6.2	2000
6 14L 14R 2 22 4 A 26 27.3 33.5 6.2 1040	4	10L	10R	2	22	4	Α	42	14.9	21.1	6.2	1680
	5	12L	12R	2	22	4	Α	34	21.1	27.3	6.2	1360
	6	14L	14R	2	22	4	Α	26	27.3	33.5	6.2	1040
7 2L 2R 0 26 3 A 0 33.5 42.0 8.5 0	7	2L	2R	0	26	3	Α	0	33.5	42.0	8.5	0

1     2L     2R     0     30     3     B     0     42.0     24.0     -18.0     0       2     10L     10R     2     22     3     B     42     24.0     17.8     -6.2     1680       3     8L     8R     2     22     4     B     50     17.8     11.6     -6.2     2000       4     6L     6R     2     18     3     B     58     11.6     6.5     -5.1     2320       5     4L     4R     2     14     4     B     66     6.5     2.6     -3.9     2640
3 8L 8R 2 22 4 B 50 17.8 11.6 -6.2 2000 4 6L 6R 2 18 3 B 58 11.6 6.5 -5.1 2320
4 6L 6R 2 18 3 B 58 11.6 6.5 -5.1 2320
5 4L 4R 2 14 4 B 66 6.5 2.6 -3.9 2640
6 2L 2R 0 14 4 B 0 2.6 0.0 -2.6 0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 40 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	3.85	1.35	1.02	1.02	1.35	3.85



