

## **LAHDEN KESA 2023 - 2 JAKSO**



Oil Pattern Distance **Forward Oil Total Tank Configuration** 

42 11.025 mL Multi Tank

**Reverse Brush Drop Reverse Oil Total Tank A Conditioner** 

33 12.33 mL **TERRAIN**  Oil Per Board **Volume Oil Total Tank B Conditioner** 

45 ul 23.355 mL **ICE** 

1 2L 2R 2 14 3 A 74 0.0 1.9 1.9 3330   2 3L 5R 2 18 3 A 66 1.9 7.0 5.1 2970   3 6L 8R 2 18 3 A 54 7.0 12.1 5.1 2430   4 10L 10R 1 18 3 A 21 12.1 14.6 2.5 945   5 12L 12R 1 22 3 A 17 14.6 17.7 3.1 765   6 14L 14R 1 22 3 A 13 17.7 20.8 3.1 585   7 2L 2R 0 26 3 A 0 20.8 42.0 21.2 0							CROSSED	START	END	FEET	T.OIL
3 6L 8R 2 18 3 A 54 7.0 12.1 5.1 2430   4 10L 10R 1 18 3 A 21 12.1 14.6 2.5 945   5 12L 12R 1 22 3 A 17 14.6 17.7 3.1 765   6 14L 14R 1 22 3 A 13 17.7 20.8 3.1 585	2L	2R	2	14	3	Α	74	0.0	1.9	1.9	3330
4 10L 10R 1 18 3 A 21 12.1 14.6 2.5 945   5 12L 12R 1 22 3 A 17 14.6 17.7 3.1 765   6 14L 14R 1 22 3 A 13 17.7 20.8 3.1 585	3L	5R	2	18	3	Α	66	1.9	7.0	5.1	2970
5 12L 12R 1 22 3 A 17 14.6 17.7 3.1 765 6 14L 14R 1 22 3 A 13 17.7 20.8 3.1 585	6L	8R	2	18	3	Α	54	7.0	12.1	5.1	2430
6 14L 14R 1 22 3 A 13 17.7 20.8 3.1 585	10L	10R	1	18	3	Α	21	12.1	14.6	2.5	945
	12L	12R	1	22	3	Α	17	14.6	17.7	3.1	765
7 2L 2R 0 26 3 A 0 20.8 42.0 21.2 0	14L	14R	1	22	3	Α	13	17.7	20.8	3.1	585
	2L	2R	0	26	3	Α	0	20.8	42.0	21.2	0
		6L 10L 12L 14L	6L 8R 10L 10R 12L 12R 14L 14R	6L 8R 2 10L 10R 1 12L 12R 1 14L 14R 1	6L 8R 2 18 10L 10R 1 18 12L 12R 1 22 14L 14R 1 22	6L 8R 2 18 3 10L 10R 1 18 3 12L 12R 1 22 3 14L 14R 1 22 3	6L 8R 2 18 3 A 10L 10R 1 18 3 A 12L 12R 1 22 3 A 14L 14R 1 22 3 A	6L 8R 2 18 3 A 54 10L 10R 1 18 3 A 21 12L 12R 1 22 3 A 17 14L 14R 1 22 3 A 13	6L 8R 2 18 3 A 54 7.0 10L 10R 1 18 3 A 21 12.1 12L 12R 1 22 3 A 17 14.6 14L 14R 1 22 3 A 13 17.7	6L 8R 2 18 3 A 54 7.0 12.1   10L 10R 1 18 3 A 21 12.1 14.6   12L 12R 1 22 3 A 17 14.6 17.7   14L 14R 1 22 3 A 13 17.7 20.8	6L 8R 2 18 3 A 54 7.0 12.1 5.1   10L 10R 1 18 3 A 21 12.1 14.6 2.5   12L 12R 1 22 3 A 17 14.6 17.7 3.1   14L 14R 1 22 3 A 13 17.7 20.8 3.1

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	42.0	31.0	-11.0	0
2	12L	12R	2	22	3	В	34	31.0	24.8	-6.2	1530
3	9L	9R	2	22	3	В	46	24.8	18.6	-6.2	2070
4	6L	6R	3	18	4	В	87	18.6	11.0	-7.6	3915
5	2L	4R	2	14	3	В	70	11.0	7.1	-3.9	3150
6	2L	2R	1	14	3	В	37	7.1	5.2	-1.9	1665
7	2L	2R	0	14	3	В	0	5.2	0.0	-5.2	0

Cleaner Ratio Main Mix 24:1 Forward Cleaner Ratio Back End Mix 33:1 Reverse Cleaner Ratio Back End Distance 50 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200





