



Oil Pattern Distance	36	Reverse Brush Drop	30	Oil Per Board	40 ul
Forward Oil Total	12.44 mL	Reverse Oil Total	10.28 mL	Volume Oil Total	22.72 mL
Tank Configuration	Multi Tank	Tank A Conditioner	TERRAIN	Tank B Conditioner	ICE

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	14	3	A	74	0.0	1.9	1.9	2960
2	2L	4R	2	18	3	A	70	1.9	7.0	5.1	2800
3	5L	7R	2	18	3	A	58	7.0	12.1	5.1	2320
4	8L	8R	2	18	3	A	50	12.1	17.2	5.1	2000
5	10L	10R	2	22	3	A	42	17.2	23.4	6.2	1680
6	12L	12R	1	22	3	A	17	23.4	26.5	3.1	680
7	2L	2R	0	26	3	A	0	26.5	36.0	9.5	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	B	0	36.0	29.0	-7.0	0
2	10L	10R	3	22	3	B	63	29.0	19.7	-9.3	2520
3	6L	6R	3	22	3	B	87	19.7	10.4	-9.3	3480
4	2L	4R	2	18	3	B	70	10.4	5.3	-5.1	2800
5	2L	2R	1	18	3	B	37	5.3	2.8	-2.5	1480
6	2L	2R	0	14	3	B	0	2.8	0.0	-2.8	0



Cleaner Ratio Main Mix 24:1 Forward
 Cleaner Ratio Back End Mix 33:1 Reverse
 Cleaner Ratio Back End Distance 50 Combined
 Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.13	1.16	1	1	1.16	2.56

