

FALCONS TAMMIKISA 2024



Oil Pattern Distance Forward Oil Total Tank Configuration

1350

40 12.16 mL Multi Tank Reverse Brush Drop Reverse Oil Total Tank A Conditioner

9.84 mL TERRAIN

31

Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 22 mL ICE

25

22

45

8

35

8

25

20

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	18	3	Α	74	0.0	2.5	2.5	2960
2	3L	5R	2	18	3	Α	66	2.5	7.6	5.1	2640
3	5L	7R	2	18	3	Α	58	7.6	12.7	5.1	2320
4	10L	10R	2	18	3	Α	42	12.7	17.8	5.1	1680
5	10L	10R	2	22	3	Α	42	17.8	24.0	6.2	1680
6	15L	15R	1	22	3	Α	11	24.0	27.1	3.1	440
7	15L	15R	1	22	3	Α	11	27.1	30.2	3.1	440
8	2L	2R	0	30	3	Α	0	30.2	40.0	9.8	0

3 15L 15R 1 22 3 B 11 24.9 21.8 -3.1		LAKI	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 15L 15R 1 22 3 B 11 24.9 21.8 -3.1 4 10L 10R 2 18 3 B 42 21.8 16.7 -5.1 16 5 8L 8R 2 18 3 B 50 16.7 11.6 -5.1 20 6 5L 5R 2 14 3 B 62 11.6 7.7 -3.9 24	1 21	L	2R	0	30	3	В	0	40.0	28.0	-12.0	0
4 10L 10R 2 18 3 B 42 21.8 16.7 -5.1 16 5 8L 8R 2 18 3 B 50 16.7 11.6 -5.1 20 6 5L 5R 2 14 3 B 62 11.6 7.7 -3.9 24	2 15	5L	15R	1	22	3	В	11	28.0	24.9	-3.1	440
5 8L 8R 2 18 3 B 50 16.7 11.6 -5.1 20 6 5L 5R 2 14 3 B 62 11.6 7.7 -3.9 24	3 15	5L	15R	1	22	3	В	11	24.9	21.8	-3.1	440
6 5L 5R 2 14 3 B 62 11.6 7.7 -3.9 24	4 10	0L	10R	2	18	3	В	42	21.8	16.7	-5.1	1680
	5 81	L	8R	2	18	3	В	50	16.7	11.6	-5.1	2000
7 2L 4R 2 14 3 B 70 7.7 3.8 -3.9 28	6 5 1	L	5R	2	14	3	В	62	11.6	7.7	-3.9	2480
	7 21	L	4R	2	14	3	В	70	7.7	3.8	-3.9	2800
8 2L 2R 0 14 3 B 0 3.8 0.0 -3.8	8 21	L	2R	0	14	3	В	0	3.8	0.0	-3.8	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 50 Combined
Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.62	1.41	1.08	1.08	1.41	3.44

