

LK 80V 2024



Oil Pattern Distance
Forward Oil Total
Tank Configuration

11.84 mL Multi Tank

39

Reverse Brush Drop Reverse Oil Total Tank A Conditioner 32 10.04 mL TERRAIN Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 21.88 mL ICE

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	18	3	Α	74	0.0	2.5	2.5	2960
2	3L	5R	3	18	3	Α	99	2.5	10.1	7.6	3960
3	7L	7R	3	18	3	Α	81	10.1	17.7	7.6	3240
4	10L	10R	2	22	3	Α	42	17.7	23.9	6.2	1680
5	2L	2R	0	26	3	Α	0	23.9	39.0	15.1	0

1		STOP 2R	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2D	_								
		ZN	0	30	3	В	0	39.0	29.0	-10.0	0
2	12L	12R	1	26	3	В	17	29.0	25.4	-3.6	680
3	11L	11R	2	22	3	В	38	25.4	19.2	-6.2	1520
4	8L	8R	3	18	3	В	75	19.2	11.6	-7.6	3000
5	7L	7R	2	18	3	В	54	11.6	6.5	-5.1	2160
6	5L	5R	1	18	3	В	31	6.5	4.0	-2.5	1240
7	2L	3R	1	18	4	В	36	4.0	1.5	-2.5	1440
8	2L	2R	0	14	4	В	0	1.5	0.0	-1.5	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 50 Combined
Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Reverse Combined

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R	
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside	
Track Zone Ratio	2.63	1.16	1	1	1.16	3.13	



