

## **VET KESÄTIISTAI TOUKOKUU 2024**



Oil Pattern Distance **Forward Oil Total Tank Configuration** 

36 9.81 mL Multi Tank

**Reverse Brush Drop Reverse Oil Total Tank A Conditioner** 

30 9.585 mL **TERRAIN**  Oil Per Board **Volume Oil Total Tank B Conditioner** 

45 ul 19.395 mL **ICE** 

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	3L	3R	2	18	3	Α	70	0.0	2.5	2.5	3150
2	6L	6R	3	18	3	Α	87	2.5	10.1	7.6	3915
3	9L	9R	1	22	3	Α	23	10.1	13.2	3.1	1035
4	10L	10R	1	26	3	Α	21	13.2	16.8	3.6	945
5	12L	12R	1	26	3	Α	17	16.8	20.4	3.6	765
6	2L	2R	0	30	3	Α	0	20.4	36.0	15.6	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	36.0	27.0	-9.0	0
2	12L	12R	2	18	3	В	34	27.0	21.9	-5.1	1530
3	10L	10R	3	18	3	В	63	21.9	14.3	-7.6	2835
4	6L	6R	4	14	3	В	116	14.3	6.4	-7.9	5220
5	2L	2R	0	14	3	В	0	6.4	0.0	-6.4	0

Cleaner Ratio Main Mix 24:1 Forward Cleaner Ratio Back End Mix 33:1 Reverse Cleaner Ratio Back End Distance 45 Combined Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200





