

LFK ERIKOISKILPAILU 2024



Oil Pattern Distance Forward Oil Total Tank Configuration 42 10.755 mL Multi Tank Reverse Brush Drop Reverse Oil Total Tank A Conditioner 35 11.79 mL TERRAIN Oil Per Board Volume Oil Total Tank B Conditioner 45 ul 22.545 mL ICE

1 2L 2R 1 18 3 A 37 0.0 0.0 0.0 166 2 3L 4R 2 18 3 A 68 0.0 5.1 5.1 306 3 6L 9R 3 18 3 A 78 5.1 12.7 7.6 351 4 12L 12R 2 22 3 A 34 12.7 18.9 6.2 153 5 14L 14R 1 22 3 A 13 18.9 22.0 3.1 58 6 16L 16R 1 22 3 A 9 22.0 25.1 3.1 40
3 6L 9R 3 18 3 A 78 5.1 12.7 7.6 351 4 12L 12R 2 22 3 A 34 12.7 18.9 6.2 153 5 14L 14R 1 22 3 A 13 18.9 22.0 3.1 58
4 12L 12R 2 22 3 A 34 12.7 18.9 6.2 153 5 14L 14R 1 22 3 A 13 18.9 22.0 3.1 58
5 14L 14R 1 22 3 A 13 18.9 22.0 3.1 58
6 16L 16R 1 22 3 A 9 22.0 25.1 3.1 40
7 2L 2R 0 30 3 A 0 25.1 42.0 16.9

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	42.0	33.0	-9.0	0
2	12L	12R	2	22	3	В	34	33.0	26.8	-6.2	1530
3	10L	10R	2	18	3	В	42	26.8	21.7	-5.1	1890
4	8L	8R	2	18	3	В	50	21.7	16.6	-5.1	2250
5	4L	4R	3	18	3	В	99	16.6	9.0	-7.6	4455
6	2L	2R	1	14	3	В	37	9.0	7.1	-1.9	1665
7	2L	2R	0	14	3	В	0	7.1	0.0	-7.1	0

Cleaner Ratio Main Mix 24:1 Cleaner Ratio Back End Mix 33:1 Cleaner Ratio Back End Distance 45 Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Forward Reverse Combined

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.63	1.43	1.04	1.04	1.49	3.33



