

VET KESÄTIISTAI KESÄKUU 2024



Oil Pattern Distance **Forward Oil Total Tank Configuration**

40 10.845 mL Multi Tank

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

10.485 mL **TERRAIN**

30

Oil Per Board **Volume Oil Total Tank B Conditioner**

45 ul 21.33 mL **ICE**

25

20

45

8

35

8

25

2

START STOP LOADS SPEED BUFFER TANK CROSSED START END FEET T.OIL 1 3L 3R 2 18 3 A 70 0.0 2.5 2.5 3150 2 6L 6R 3 18 3 A 87 2.5 10.1 7.6 3915 3 9L 9R 2 22 3 A 46 10.1 16.3 6.2 2070 4 10L 10R 1 26 3 A 21 16.3 19.9 3.6 945 5 12L 12R 1 26 3 A 17 19.9 23.5 3.6 765 5 2L 2R 0 30 3 A 0 23.5 40.0 16.5 0
2 6L 6R 3 18 3 A 87 2.5 10.1 7.6 3915 3 9L 9R 2 22 3 A 46 10.1 16.3 6.2 2070 4 10L 10R 1 26 3 A 21 16.3 19.9 3.6 945 5 12L 12R 1 26 3 A 17 19.9 23.5 3.6 765
3 9L 9R 2 22 3 A 46 10.1 16.3 6.2 2070 4 10L 10R 1 26 3 A 21 16.3 19.9 3.6 945 5 12L 12R 1 26 3 A 17 19.9 23.5 3.6 765
1 10L 10R
5 12L 12R 1 26 3 A 17 19.9 23.5 3.6 765
5 2L 2R 0 30 3 A 0 23.5 40.0 16.5 0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	40.0	31.0	-9.0	0
2	14L	14R	2	22	3	В	26	31.0	24.8	-6.2	1170
3	12L	12R	3	18	3	В	51	24.8	17.2	-7.6	2295
4	10L	10R	3	18	3	В	63	17.2	9.6	-7.6	2835
5	5L	5R	3	14	3	В	93	9.6	3.7	-5.9	4185
6	2L	2R	0	14	3	В	0	3.7	0.0	-3.7	0

Cleaner Ratio Main Mix 24:1 Cleaner Ratio Back End Mix 33:1 Cleaner Ratio Back End Distance 45 Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Forward Reverse Combined

	Г
R:7R-3R Outside	

3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R Item Outside:Middle Middle:Middle Description Inside:Middle MIddle: Inside Middle:Middle Middle:0 1.56 1.02 1.02 Track Zone Ratio 1.56

