

VET KESÄTIISTAI HEINÄKUU 2024



Oil Pattern Distance **Forward Oil Total Tank Configuration**

43 10.125 mL Multi Tank **Reverse Brush Drop Reverse Oil Total Tank A Conditioner**

31 11.34 mL **TERRAIN** Oil Per Board **Volume Oil Total Tank B Conditioner**

45 ul 21.465 mL **ICE**

1 3L 3R 2 18 3 A 70 0.0 2.5 2.5 3150 2 8L 8R 3 18 3 A 75 2.5 10.1 7.6 3375 3 9L 9R 2 22 3 A 46 10.1 16.3 6.2 2070 4 11L 11R 1 26 3 A 19 16.3 19.9 3.6 855 5 13L 13R 1 26 3 A 15 19.9 23.5 3.6 675 6 2L 2R 0 30 3 A 0 23.5 43.0 19.5 0		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 9L 9R 2 22 3 A 46 10.1 16.3 6.2 2070 4 11L 11R 1 26 3 A 19 16.3 19.9 3.6 855 5 13L 13R 1 26 3 A 15 19.9 23.5 3.6 675	1	3L	3R	2	18	3	Α	70	0.0	2.5	2.5	3150
4 11L 11R 1 26 3 A 19 16.3 19.9 3.6 855 5 13L 13R 1 26 3 A 15 19.9 23.5 3.6 675	2	8L	8R	3	18	3	Α	75	2.5	10.1	7.6	3375
5 13L 13R 1 26 3 A 15 19.9 23.5 3.6 675	3	9L	9R	2	22	3	Α	46	10.1	16.3	6.2	2070
	4	11L	11R	1	26	3	Α	19	16.3	19.9	3.6	855
6 2L 2R 0 30 3 A 0 23.5 43.0 19.5 0	5	13L	13R	1	26	3	Α	15	19.9	23.5	3.6	675
	6	2L	2R	0	30	3	Α	0	23.5	43.0	19.5	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	43.0	34.0	-9.0	0
2	14L	14R	3	22	3	В	39	34.0	24.7	-9.3	1755
3	12L	12R	3	18	3	В	51	24.7	17.1	-7.6	2295
4	10L	10R	3	18	3	В	63	17.1	9.5	-7.6	2835
5	4L	4R	3	14	3	В	99	9.5	3.6	-5.9	4455
6	2L	2R	0	14	3	В	0	3.6	0.0	-3.6	0

Cleaner Ratio Main Mix Forward 24:1 Cleaner Ratio Back End Mix 33:1 Reverse Cleaner Ratio Back End Distance 45 Combined

Buffer RPM:	4 = 650 3	8 = 500 2 =	300 1 = 20	00			
Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R	
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside	
Track Zone Ratio	4.77	1.69	1.03	1.03	1.69	4.77	
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside	



