

## **STARK OPEN**



Oil Pattern Distance 41 **Reverse Brush Drop** 32 Oil Per Board 50 ul **Volume Oil Total Forward Oil Total** 12.25 mL **Reverse Oil Total** 10.95 mL 23.2 mL **Tank Configuration Tank A Conditioner TERRAIN Tank B Conditioner** Multi Tank **ICE** 

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	1	14	3	Α	37	0.0	0.0	0.0	1850
2	5L	5R	3	18	3	Α	93	0.0	7.6	7.6	4650
3	10L	10R	3	18	3	Α	63	7.6	15.2	7.6	3150
4	13L	13R	2	18	3	Α	30	15.2	20.3	5.1	1500
5	15L	15R	2	22	3	Α	22	20.3	26.5	6.2	1100
6	2L	2R	0	30	3	Α	0	26.5	41.0	14.5	0

1 2L     2R     0     30     3 B     0     41.0     30.0     -11.0     0       2 12L     12R     3     22     3 B     51     30.0     20.7     -9.3     2550       3 9L     9R     2     22     3 B     46     20.7     14.5     -6.2     2300       4 7L     7R     2     22     3 B     54     14.5     8.3     -6.2     2700       5 5L     5R     1     18     3 B     31     8.3     5.8     -2.5     1550       6 2L     2R     1     18     3 B     37     5.8     3.3     -2.5     1850												
2     12L     12R     3     22     3     B     51     30.0     20.7     -9.3     2550       3     9L     9R     2     22     3     B     46     20.7     14.5     -6.2     2300       4     7L     7R     2     22     3     B     54     14.5     8.3     -6.2     2700       5     5L     5R     1     18     3     B     31     8.3     5.8     -2.5     1550       6     2L     2R     1     18     3     B     37     5.8     3.3     -2.5     1850		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 9L     9R     2 22     3 B     46 20.7 14.5 -6.2 2300       4 7L     7R     2 22     3 B     54 14.5 8.3 -6.2 2700       5 5L     5R     1 18     3 B     31 8.3 5.8 -2.5 1550       6 2L     2R     1 18     3 B     37 5.8 3.3 -2.5 1850	1	2L	2R	0	30	3	В	0	41.0	30.0	-11.0	0
4 7L     7R     2 22     3 B     54 14.5 8.3 -6.2 2700       5 5L     5R     1 18 3 B     31 8.3 5.8 -2.5 1550       6 2L     2R     1 18 3 B     37 5.8 3.3 -2.5 1850	2	12L	12R	3	22	3	В	51	30.0	20.7	-9.3	2550
5 5L 5R 1 18 3 B 31 8.3 5.8 -2.5 1550 6 2L 2R 1 18 3 B 37 5.8 3.3 -2.5 1850	3	9L	9R	2	22	3	В	46	20.7	14.5	-6.2	2300
6 2L 2R 1 18 3 B 37 5.8 3.3 -2.5 1850	4	7L	7R	2	22	3	В	54	14.5	8.3	-6.2	2700
	5	5L	5R	1	18	3	В	31	8.3	5.8	-2.5	1550
7 2L 2R 0 14 3 B 0 3.3 0.0 -3.3 0	6	2L	2R	1	18	3	В	37	5.8	3.3	-2.5	1850
	7	2L	2R	0	14	3	В	0	3.3	0.0	-3.3	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 50 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	4.17	1.67	1.04	1.04	1.67	4.17



