



VET KESÄTIISTAI HEINÄKUU 2025



Oil Pattern Distance	43	Reverse Brush Drop	33	Oil Per Board	40 uL
Forward Oil Total	10.24 mL	Reverse Oil Total	9.52 mL	Volume Oil Total	19.76 mL
Tank Configuration	Multi Tank	Tank A Conditioner	TERRAIN	Tank B Conditioner	ICE

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	4L	4R	2	18	3	A	66	0.0	2.5	2.5	2640
2	6L	6R	2	18	3	A	58	2.5	7.6	5.1	2320
3	10L	10R	3	22	3	A	63	7.6	16.9	9.3	2520
4	12L	12R	2	22	3	A	34	16.9	23.1	6.2	1360
5	14L	14R	2	22	3	A	26	23.1	29.3	6.2	1040
6	16L	16R	1	26	3	A	9	29.3	32.9	3.6	360
7	2L	2R	0	26	3	A	0	32.9	43.0	10.1	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	B	0	43.0	30.0	-13.0	0
2	12L	12R	2	22	3	B	34	30.0	23.8	-6.2	1360
3	10L	10R	2	18	3	B	42	23.8	18.7	-5.1	1680
4	9L	9R	2	18	3	B	46	18.7	13.6	-5.1	1840
5	8L	8R	2	18	3	B	50	13.6	8.5	-5.1	2000
6	4L	4R	2	14	3	B	66	8.5	4.6	-3.9	2640
7	2L	2R	0	14	3	B	0	4.6	0.0	-4.6	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 30 Combined
Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5.5	1.64	1.05	1.05	1.64	5.5

