

## VKS SYYSKUU LAHTI



Oil Pattern Distance Forward Oil Total Tank Configuration

13.635 mL Multi Tank

41

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

36 12.915 mL TERRAIN Oil Per Board Volume Oil Total Tank B Conditioner 45 ul 26.55 mL ICE

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL	
1	2L	2R	2	18	3	Α	74	0.0	2.5	2.5	3330	
2	3L	5R	1	18	3	Α	33	2.5	5.0	2.5	1485	
3	5L	7R	2	18	3	Α	58	5.0	10.1	5.1	2610	
4	2L	2R	2	18	3	Α	74	10.1	15.2	5.1	3330	
5	12L	12R	2	22	3	Α	34	15.2	21.4	6.2	1530	
6	13L	13R	2	22	3	Α	30	21.4	27.6	6.2	1350	
7	2L	2R	0	26	3	Α	0	27.6	41.0	13.4	0	

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	41.0	34.0	-7.0	0
2	11L	11R	2	22	3	В	38	34.0	27.8	-6.2	1710
3	10L	10R	2	22	3	В	42	27.8	21.6	-6.2	1890
4	8L	8R	2	18	3	В	50	21.6	16.5	-5.1	2250
5	7L	7R	2	18	4	В	54	16.5	11.4	-5.1	2430
6	5L	5R	1	18	4	В	31	11.4	8.9	-2.5	1395
7	2L	3R	2	18	4	В	72	8.9	3.8	-5.1	3240
8	2L	2R	0	14	4	В	0	3.8	0.0	-3.8	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.39	1.34	1	1	1.34	2.75



