

MISTA HELPOMMALLA OPEN



Oil Pattern Distance Forward Oil Total Tank Configuration

12.33 mL Multi Tank

41

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

11.295 mL TERRAIN

32

Oil Per Board Volume Oil Total Tank B Conditioner 45 ul 23.625 mL ICE

25

22

45

\$

35

8

25

2

9

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	3L	4R	2	18	3	Α	68	0.0	2.5	2.5	3060
2	5L	6R	2	18	3	Α	60	2.5	7.6	5.1	2700
3	8L	9R	2	18	3	Α	48	7.6	12.7	5.1	2160
4	10L	10R	2	22	3	Α	42	12.7	18.9	6.2	1890
5	12L	12R	2	22	3	Α	34	18.9	25.1	6.2	1530
6	15L	15R	1	22	3	Α	11	25.1	28.2	3.1	495
7	15L	15R	1	22	3	Α	11	28.2	31.3	3.1	495
8	2L	2R	0	30	3	Α	0	31.3	41.0	9.7	0

1 2L 2R 0 30 3 B 0 41.0 30.0 -11.0 2 15L 15R 1 22 3 B 11 30.0 26.9 -3.1	START										
2 15L 15R 1 22 3 B 11 30.0 26.9 -3.1 4 3 15L 15R 1 18 3 B 11 26.9 24.4 -2.5 4 4 10L 10R 2 18 3 B 42 24.4 19.3 -5.1 18 5 10L 10R 3 18 3 B 63 19.3 11.7 -7.6 28 6 5L 5R 2 14 3 B 62 11.7 7.8 -3.9 27 7 5L 5R 2 14 3 B 62 7.8 3.9 -3.9 27		STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 15L 15R 1 18 3 B 11 26.9 24.4 -2.5 4 4 10L 10R 2 18 3 B 42 24.4 19.3 -5.1 18 5 10L 10R 3 18 3 B 63 19.3 11.7 -7.6 28 6 5L 5R 2 14 3 B 62 11.7 7.8 -3.9 27 7 5L 5R 2 14 3 B 62 7.8 3.9 -3.9 27	1 2L	2R	0	30	3	В	0	41.0	30.0	-11.0	0
4 10L 10R 2 18 3 B 42 24.4 19.3 -5.1 18 5 10L 10R 3 18 3 B 63 19.3 11.7 -7.6 28 6 5L 5R 2 14 3 B 62 11.7 7.8 -3.9 27 7 5L 5R 2 14 3 B 62 7.8 3.9 -3.9 27	2 15L	15R	1	22	3	В	11	30.0	26.9	-3.1	495
5 10L 10R 3 18 3 B 63 19.3 11.7 -7.6 28 6 5L 5R 2 14 3 B 62 11.7 7.8 -3.9 27 7 5L 5R 2 14 3 B 62 7.8 3.9 -3.9 27	3 15L	15R	1	18	3	В	11	26.9	24.4	-2.5	495
6 5L 5R 2 14 3 B 62 11.7 7.8 -3.9 27 7 5L 5R 2 14 3 B 62 7.8 3.9 -3.9 27	4 10L	10R	2	18	3	В	42	24.4	19.3	-5.1	1890
7 5L 5R 2 14 3 B 62 7.8 3.9 -3.9 27	5 10L	10R	3	18	3	В	63	19.3	11.7	-7.6	2835
	6 5L	5R	2	14	3	В	62	11.7	7.8	-3.9	2790
8 2L 2R 0 14 3 B 0 3.9 0.0 -3.9	7 5L	5R	2	14	3	В	62	7.8	3.9	-3.9	2790
	8 2L	2R	0	14	3	В	0	3.9	0.0	-3.9	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 35 Combined

Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

-7.6 -3.9	1890 5 2835 9 2790 9 2790				
rwai vers mbi	se				
-13R	18L-18R:12R-8R	18L-18R:7R-3R			
le	Middle:Middle	Middle:Outside			
	1.62	4.79			

