

## **GM SÄHKÖ OPEN 2025**



Oil Pattern Distance Forward Oil Total Tank Configuration 41 10.76 mL Multi Tank Reverse Brush Drop Reverse Oil Total Tank A Conditioner 35 10.84 mL TERRAIN Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 21.6 mL ICE

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	14	3	Α	74	0.0	1.9	1.9	2960
2	4L	6R	3	18	3	Α	93	1.9	9.5	7.6	3720
3	10L	10R	2	22	3	Α	42	9.5	15.7	6.2	1680
4	12L	12R	2	22	3	Α	34	15.7	21.9	6.2	1360
5	14L	14R	2	22	3	Α	26	21.9	28.1	6.2	1040
6	2L	2R	0	26	3	Α	0	28.1	41.0	12.9	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	В	0	41.0	32.0	-9.0	0
2	13L	13R	1	26	3	В	15	32.0	28.4	-3.6	600
3	11L	11R	2	22	3	В	38	28.4	22.2	-6.2	1520
4	8L	8R	1	22	3	В	25	22.2	19.1	-3.1	1000
5	7L	7R	1	22	3	В	27	19.1	16.0	-3.1	1080
6	6L	6R	1	22	3	В	29	16.0	12.9	-3.1	1160
7	5L	5R	1	18	3	В	31	12.9	10.4	-2.5	1240
8	4L	4R	1	18	3	В	33	10.4	7.9	-2.5	1320
9	2L	3R	1	18	3	В	36	7.9	5.4	-2.5	1440
10	2L	2R	1	18	3	В	37	5.4	2.9	-2.5	1480
11	2L	2R	0	14	3	В	0	2.9	0.0	-2.9	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 50 Combined
Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R Item Outside:Middle Middle:Middle Middle:Middle Middle:Outside Description Inside:Middle MIddle: Inside 2.5 1.46 1.02 1.02 2.92 Track Zone Ratio 1.46



